

LSU155/255/275/355/395

When professional power is needed

- commercial wet and dry vacuum cleaners



PART OF THE NILFISK GROUP

VIPER



Model description: First number stands for number of motors, second two numbers tells the tank size.
LSU135 is equipped with one suction motor and a 35 liter tank capacity

LSU155/255/275/355/395

Volume, suction power and durability

The Viper LSU series are powerful wet and dry professional vacuum cleaners that is easy to use and has a robust design. The machines are available in 4 different tank sizes and various motor alternatives so that you can pick exactly the size and power that suits your cleaning needs.

The larger trolley mounted machines come with a drain hose mounted so you can easily empty the tank without taking off the motor top.

All machines are equipped with sturdy rear wheels and rotating front wheels which makes them light and easy to maneuver.

- For wet or dry vacuum application
- Easy to use and service
- Optimal suction power
- Robust tanks in stainless steel or plastic
- Cable storage
- Different tank sizes with different motor alternatives



Robust handle with cable storage hook and individual switches for the suction motors



Easy storage of accessories



Drain hose for easy emptying of the container

Technical specifications

Description	LSU 135	LSU155
Voltage (v)	220 - 240	220 - 240
Frequency (hz)	50-60	50-60
Rated power (w)	1000	1000
Vacuum motor (type):	2-stage	2-stage
Vacuum (mmH2O)	2020	2115
Air flow (ltr.min)	1869	2152
Power cable length (m)	7	7
Power cable color	orange	orange
Tank capacity (ltr.)	35	55
Sound level (dB(A))	74	74
Amp draw (Amp)	4.6	4.6
Net weight (kg)	13	22
Length x Width x Height (cm)	47x45x80	63x59x95
Reference		
Steel version	50000110	50000118
Plastic version	50000111	50000119

Technical specifications

Description	LSU255	LSU275
Voltage (v)	220 - 240	220 - 240
Frequency (hz)	50-60	50-60
Rated power (w)	2000	2000
Vacuum motor (type):	2-stage	2-stage
Vacuum (mmH2O)	2250	2250
Air flow (ltr.min)	3115	3115
Power cable length (m)	8	8
Power cable color	orange	orange
Tank capacity (ltr.)	55	75
Sound level (dB(A))	78	78
Amp draw (Amp)	4.6/9.2	4.6/9.2
Net weight (kg)	24.5	25
Length x Width x Height (cm)	63x59x95	63x59x99
Reference		
Steel version	50000126	50000134
Plastic version	50000127	

Technical specifications

Description	LSU375	LSU 395
Voltage (v)	220 - 240	220 - 240
Frequency (hz)	50-60	50-60
Rated power (w)	3000	3000
Vacuum motor (type):	2-stage	2-stage
Vacuum (mmH2O)	2280	2280
Air flow (ltr.min)	3540	3540
Power cable length (m)	8	10
Power cable color	orange	orange
Tank capacity (ltr.)	75	95
Sound level (dB(A))	79	79
Amp draw (Amp)	4.6/9.2/13.8	4.6/9.2/13.8
Net weight (kg)	28	29.3
Length x Width x Height (cm)	63x59x99	63x59x112
Reference		
Steel version	50000140	50000150
Plastic version		50000151

Standard accessories

	LSU 135	LSU155
Round nozzle Ø38 mm	VA20803	VA20803
Crevice nozzle Ø38 mm	VA20806	VA20806
Dry pick-up nozzle Ø38 mm	VA80036	VA80036
Wet pick-up nozzle	VA80853	VA80853
Suction tube assembly	VA80401	VA80400
Steel tube kit	VA80711	VA80711
Absorbing dust filter	VA80706	VA80119

Standard accessories

	LSU255	LSU275
Round nozzle Ø38 mm	VA20803	VA20803
Crevice nozzle Ø38 mm	VA20806	VA20806
Dry pick-up nozzle Ø38 mm	VA80036	VA80036
Wet pick-up nozzle	VA80853	VA80853
Suction tube assembly	VA80400	VA80400
Steel tube kit	VA80711	VA80711
Absorbing dust filter	VA80119	VA80119

Standard accessories

	LSU375	LSU395
Round nozzle Ø38 mm	VA20803	VA20803
Crevice nozzle Ø38 mm	VA20806	VA20806
Dry pick-up nozzle Ø38 mm	VA80036	VA80036
Wet pick-up nozzle	VA80853	VA80853
Suction tube assembly	VA80400	VA80400
Steel tube kit	VA80711	VA80711
Absorbing dust filter	VA80119	VA80110

Dealer: